

Transmitter Type: Pocket-MFSL V1, V2, V3, V4, V5

Housing Style:

Ergonomically designed housing, one-hand operation

Housing Material:

Polycarbonate (PC) blend

Environmental Protection:

IP 65 (Exceeds Nema 12/13)

Weight:

Up to 0.4 lbs, 200 g (includes batteries)

Dimensions:

Length: 4.8 in., 123 mm

Height: 2.7 in., 69 mm

Depth: 1.1 in., 28 mm

Antenna:

Internal

Battery Compartment:

Separated from electronics, with sliding, heavy-duty lid

Power Supply:

3 AA batteries (3 Mignon LR6-AA 1.5 V)

Diagnostics:

Status LED for operation, low battery and Stop activation

Operation Time:

Up to 500 h

Pushbutton Configuration:

V1 - 2 dual speed + start/horn + stop

V2 - 4 dual speed + start/horn + stop

V3 - 6 single speed + start/horn + stop

V4 - 3 single speed + stop

V5 - 6 dual speed + start/horn + stop

Frequency Range:

868 MHz / 916 MHz or 311 MHz / 315 MHz (Selectable via H-Link)

RF Unit:

Type MFS with single frequency, selectable duty cycle

Power (RF Output):

< 3 mW

Typical Operating Range:

Approximately 100 ft. (30 m)

Safety Address:

20-bit (over 999,999 individual possibilities)

Permanently assigned in transmitter

Address learning receiver

Safety:

Active and passive Stop function

Parity & Checksum

Temperature Range:

-11° F ... +158° F (-25° C ... +70° C)

Humidity Range:

0 - 97% maximum non-condensing

Response Time:

Less than 100 msec.

Baud Rate:

Up to 76.8 Kbps. (selectable via H-Link)

